


# RIMPA



## top



RIMPA TOP industrial luminaire with increased efficiency dedicated to work in extremely harsh environment. The housing is hermetic, resistant to high ambient temperature and well protected against mechanical impacts. Rimpa is light, enables simple installation and is easy to keep clean.

### Example applications:

Industrial, commercial, production facilities, communication lines, rooms with high humidity, temperature and dust.

Name	Power [W]	Luminous flux	Protection class	IP	IK	CRI	CCT	Luminous efficiency up to
RIMPA TOP Transparent	20	3 500 lm	I	IP67	IK10	>80	4000K	175 lm/W
RIMPA TOP Frosted	20	3 000 lm	I	IP67	IK10	>80	4000K	150 lm/w
RIMPA TOP Transparent	40	7 000 lm	I	IP67	IK10	>80	4000K	175 lm/W
RIMPA TOP Frosted	40	6 000 lm	I	IP67	IK10	>80	4000K	150 lm/W

Different parameters on request.

**Installation:** suspended / surface mounted / accessory

**Supply voltage:** 230V AC / 50-60Hz

**Ambient temperature range:** -20°C...+50°C

**Lifetime L80B50:** 60 000h

**Power factor:** >0,9

**Housing:** PC

**Power Supply:** DALI driver in option


**Warranty:** 5 years

### Dimensional drawing:


Name	L	F	C	H	W	G	Weight
RIMPA 20	650	15	685	115	75	85	0,9 kg
RIMPA 40	1240	15	1280	115	75	85	1,7 kg

### Light beam curves:

Transparent



Frosted



SUSPENDED



SURFACE MOUNTED



Luminous flux tolerance +/-10%

Our products are constantly upgraded. We reserve right to any construction changes without previous notice.