PERFAND LED®

UVIA


UVIA is a LED ceiling lamp characterized by a solid structure, which makes it ideal for various types of rooms, passageways or corridors. The degree of protection IP65 and resistance IK08 allows it to be used in rooms with high humidity and outside buildings. The functionality of the ceiling is complemented by a built-in microwave motion sensor, which automatically turns off the luminaire when no person is within the range of the sensor or when it is already bright enough in the room. In addition, the luminaire is equipped with a 12/16 W power switch, as well as the ability to set the color temperature depending on the need for 3000 K / 4000 K / 6500 K.





Application example:

Stairways, passageways, public utility buildings.



Name	Power	Luminous flux	Protection class	IP	IK	CRI	сст	Luminous efficacy
UVIA	12 / 16 W	1200 / 1600 lm	II	65	08	>80	3000 / 4000 / 6500 K	100 lm / W

Technical parameters:


Power supply: 230 V AC / 50-60 Hz Working temperature: -30°C... +45°C

Lifetime: > 30 000 h Power factor: >0,9 Installation: surface

Housing: PC

Warranty: 3 years

00 h



Dimensional drawing:

NAME	D	H	WEIGHT	
	(mm)	(mm)	(kg)	
UVIA	330	82	1,1	

Light distribution curves:

Frosted 109 90 90 75 75 76 45 240 45 45 300 15 0 115 30 11 = 100%

Our products are constantly being improved. We reserve the right to make technical changes to the luminaires without prior publication of this information. Luminous flux tolerance +/- 10%